



Juhtide ja varjestuse ristlõige [mm <sup>2</sup> ]	Standardpikkus [m]	Standardpakend	EAN/GTIN number	SAP kood
4x25/16	500	K11	6410006020218	20205617
4x35/16	500	K12	6410006020232	20205618
4x50/25	500	K12	6410006020249	20205619
4x70/35	500	K14	6410006020256	20205620
4x95/50	500	K16	6410006020263	20205621
4x120/70	500	K18	6410006020164	20205622
4x150/70	500	K20	6410006020171	20205623
4x185/95	500	K22	6410006020188	20205624
4x240/120	500	K24	6410006020201	20205625
4x300/150	500	K24	6410006020225	20205626

Juhtmete arv ja ristlõike pindala [mm <sup>2</sup> ]	Läbimõõt ca [mm]	Kaabli mass [kg/km]	Vähim lubatud painderaadius lõplikul paigaldusel [m]	Väikseim lubatud painderaadius paigaldusel [m]	Takistus [Ω/km]
4x25/16	23	1400	190	280	0,727
4x35/16	26	1800	210	310	0,524
4x50/25	29	2400	230	350	0,387
4x70/35	35	3400	280	420	0,268
4x95/50	38	4600	300	460	0,193
4x120/70	42	5800	340	500	0,153
4x150/70	47	7000	380	560	0,124
4x185/95	52	8700	420	620	0,0991
4x240/120	59	12000	480	710	0,0754
4x300/150	65	14000	520	780	0,0601