

Installationskabler

PROTECH EVOLUCION RZ1-K 1kV



Approval

CE

Standard

UNE 21123 Part 4
IEC 60502-1
SS-EN 60754-1, -2
SS-EN 61034-1, -2
EN 50575:2014

Construction
Construction Standard
Corrosive gases
Smoke density
Power, control and communication cables - Cables for general applications in construction works subject to reaction to fire requirements

Features

CPR Performance class

Cca

| Conductors and screen area [mm ²] | Standard delivery length [m] | Delivery Package | EAN/GTIN number | SAP Number |
|---|------------------------------|------------------|-----------------|------------|
| 2x1,5 | 100 | Coil | 8430220087567 | 20193686 |
| 2x2,5 | 100 | Coil | 8430220087574 | 20193687 |
| 2x6 | 100 | Coil | 8430220087581 | 20193688 |
| 3G1,5 | 100 | Coil | 8430220087598 | 20193689 |
| 3G2,5 | 100 | Coil | 8430220087642 | 20193690 |
| 3G4 | 100 | Coil | 8430220087604 | 20193691 |
| 4G1,5 | 100 | Coil | 8430220087628 | 20193692 |
| 4G2,5 | 100 | Coil | 8430220087611 | 20193693 |
| 5G1,5 | 100 | Coil | 8430220087635 | 20193694 |
| 5G2,5 | 100 | Coil | 8430220087659 | 20193695 |

| Conductors and screen area [mm ²] | Diameter over sheath [mm] | Cable weight [kg/km] | Resistance [Ω/km] | Min. Bending radius during installation [mm] |
|---|---------------------------|----------------------|-------------------|--|
| 2x1,5 | 10 | 144 | 13,3 | |
| 2x2,5 | 10,9 | 179 | 7,98 | |
| 2x6 | 13 | 282 | 3,3 | |
| 3G1,5 | 10,5 | 160 | 13,3 | |
| 3G2,5 | 11,5 | 204 | 7,98 | |
| 3G4 | 12,4 | 260 | 4,95 | |
| 4G1,5 | 11,6 | 196 | 13,3 | |
| 4G2,5 | 12,8 | 251 | 7,98 | |
| 5G1,5 | 12,4 | 210 | 13,3 | |
| 5G2,5 | 13,3 | 275 | 7,98 | |