

## Installationskablar

# MCCMO-HF C-PRo 750V



### Tootepere alternatiivmärgistus

N07ZCZ1-U

### Standard

EVS-EN 50575:2014

### Temperatuur

Max töötemperatuur

90 °C

Juhtide ja varjestuse ristlõige [mm <sup>2</sup> ]	Standardpikkus [m]	Standardpakend	EAN/GTIN number	SAP kood
	500	K8	8711401056528	20231476
	500	K8	8711401056566	20231470
	500	K8	8711401056498	20231471
	500	K9	8711401056481	20231477
	500	K9	8711401056511	20231472
	500	K11	8711401056535	20231478
	500	K11	8711401056450	20231473
	500	K11	8711401056573	20231474
7x1,5	500	K8	0602092	20220120
7x1,5	1000	K9		20220121
7x2,5	500	K8	0602097	20220123
7x2,5	1000	K11	6430065751878	20220122
12x1,5	500	K9	0602093	20220117
12x1,5	1000	K11		20220116
12x2,5	500	K11	0602098	20220118
12x2,5	1000	K12		20220119
19x1,5	500	K9	0602094	20223514
19x1,5	1000	K12		20232107
19x2,5	500	K11	0602099	20228264
19x2,5	1000	K14		20232108
27x1,5	500	K11		20232109
27x2,5	500	K12	0624000	20232110
27x1,5	1000	K16		20232111

Juhtmete arv ja ristlõike pindala [mm <sup>2</sup> ]	Läbimõõt ca [mm]	Kaabli mass [kg/km]	Vähim lubatud painderaadius lõplikul paigaldusel [m]	Väikseim lubatud painderaadius paigaldusel [m]	Takistus [Ω/km]
7x1,5	15	350	120	180	12,1
7x2,5	17	470	140	210	7,41
12x1,5	18	500	150	220	12,1
12x2,5	21	700	170	260	7,41
19x1,5	21	630	170	260	12,1
19x2,5	24	940	200	290	7,41
27x1,5	24	850	200	290	12,1
27x2,5	28	1258	230	340	7,41